

SMARTEQ™

● ● ● ● ● A PCTEL Company



A = Radiator length measured inclusive coil and exclusive knob for use in combination with Bases 1123, 1131, 128, 2500 or Ant.

B = Radiator length measured inclusive coil and exclusive of knob for use in combination with magnet mount MaxiMag 130.

C = Radiator length measured inclusive coil and exclusive of knob for use in combination with MultiFin

Frequency range 68–225 MHz

F (MHz)	A(mm)	B(mm)	C(mm)
68	1055	1070	1100
70	1035	1020	1100
75	950	935	1024
80	890	870	970
85	830	810	910
90	780	760	837
95	730	710	
100	695	675	746
105	660	640	716
110	630	610	680
115	600	580	644
120	570	550	611
125	550	525	584
130	525	500	574
135	505	480	547
140	485	460	513
145	470	445	494
150	455	430	484
155	440	415	464
160	430	405	446
165	415	395	436
170	400	375	410
175	390	365	400
180	380	355	390
185	367	343	378
190	357	333	370
195	346	322	363
200	338	312	350
205	330	303	342
210	322	294	331

F (MHz)	A(mm)	B(mm)	C(mm)
215	314	287	325
220	305	280	305
225	298	273	299

Cutting table for radiator
310.06.00.00

Smarteq Wireless AB
Stockholm, Sweden

info@smarteq.se
www.smarteq.com

